



TPX 6111B

TYPE	TPX 6111B	TPX 6111C/3	TPX 6113	TPX 6113/2
BORING SPINDLE DIAMETER (mm)	110	110	130	130
SPINDLE TAPER	Morse No.6	ISO 7:24 No50	Metric 80	Metric 80
MAX. SPINDLE TORQUE (N.m.)	1225	1250	3136	3136
MAX FACING HEAD TORQUE (N.m.)	1960	1960	4900	4900
MAX SPINDLE THRUST (N)	12250	12250	31360	31360
MAX TRAVERSE OF BORING SPINDLE (mm)	600	600	900	900
NUMBER OF SPINDLE SPEEDS	22	-	24	24
RANGE OF SPINDLE SPEEDS (r/min)	8-1000	8-1100	4-800	4-800
TRAVEL OF FACING SLIDE 9mm)	180	180	250	250
TABLE WORKING SURFACE (mm)	1100x960	1250x1100	1600x1400	1800x1600
MAX. PERMISSIBLE LOAD ON TABLE (kg)	2500	3000	8000	10000
DISTANCE BETWEEN SPINDLE AXIS AND TABLE SURFACE (mm)	0 - 900	0 - 1200	0 - 1400	0 - 1800
TABLE TRAVEL (mm)	1000x900	1400x1600	1500x1600	2000x2000
MOTOR (kW)	7,5	15	15	15
WEIGHT (kg)	13000	18000	24500	29300